



## VL4 Bracket Mount



## **VL4** Bracket Mount

## PRODUCT INFORMATION:

The mid-range offering of the VL series, the VL4 has a streamline design for machines with 12-48 volt systems offering up to 825 effective lumen lights with 4 LED's. The VL4 is available with a thru bolt mount or a bracket mount to easily tilt the light to shine light where it is needed and has alternative coloured LED options in white, green or red.





**EMC TESTED** 



**IP 69K** 



**VIBRATION TESTED** 



**SALT SPRAY TESTED** 



**UL RATED OPTIONAL** 

Operating Temp: -40° to 75°C -40° to 85°C


Light Pattern: Symmetric, Asymmetric


Lens Material: Plastic

Housing: Cast Aluminium


Mounting Options: Thru Bolt


Connector: (DT04-2P) Built in







## **LIGHT BEAM PATTERNS:**









LUMEN OUTPUT		Number	VOLTAGE			AMP DRAW		Power			EMC		Vibration	Salt Spray	UL Rated
Theoretical	Effective	of LED'S	Machine		ating nge	12 Volts	24 Volts	(Watts)	Colour Temp	CRI	EN55025 CLASS	IP 69K	5-2000hZ 3 Axis	ASTMB117	Optional
900	600	4	12-48	9	60	1.2	0.6	15	5700	70	4	•	10 Grms	•	•
1100	825	4	12-48	9	60	1.2	0.6	15	5700	75	4	•	10 Grms	•	•
2600	2000	4	12-48	9	60	1.8	0.9	22	5700	70	3	•	10 Grms	•	
2600	2000	4	12	9	16	1.8		22	5700	70	5	•	10 Grms	•	
2600	2000	4	24	18	32		0.9	22	5700	70	5	•	10 Grms	•	